

SPECIFICATIONS

Capacity: 40,000 lbs. Trailer Weight: 8,380 lbs.

Deck Width 8 ft. 6 in. Length: 19 ft. Height: 34 in.

Mainrails: W14" x 22 lbs. wide flange I-Beam, one piece cold formed Frame

Hi-tensile 50,000 P.S.I. steel mainrails from front to drawbar to rear of trailer

8° Beaver Tail (Safe Low Loading Angle)

Crossmembers 6" x 3.7 lbs. per ft. I-Beam pierced through mainbeam

Decking Nominal 2" Hardwood

Headboard 8" high, full width of trailer Drawbar Storage Area

Lights Sealed L.E.D., 12 volt, DOT approved

USA Star PLUS Sealed Modular Wiring Harness w/ 7-Way ATA Plug Wiring Harness One piece solid cast steel (adjustable) lunette eye & flange mount Hitch

Two 1/2" Blue-Krome plated high test, safety hook w/ latch Safety Chains

Parking Jack 70,000 lbs. static / 40,000 lbs. lift (Heavy Duty 2-speed screw type)

Tie Down Five per side - Patented "ROTO RINGS"® Swivel 360°

Colors Black, Yellow, Blue (standard) Imron Paint

RUNNING GEAR

Eight (8) 215/75R 17.5 (H) Steel Belted Radial Tires

Hubs/Wheels Four Disc Type Hubs, Eight 6.75 x 17.5, 8-Bolt, Hub-Piloted Disc Wheels

Suspension Hutch H-9700, Three leaf, capacity 50,000 lbs. tandem

Axles Two 5" diameter 22,500 lbs. each, H.M. series bearings (maximum axle track width)

ALL WHEEL ABS Anti-Lock Brake System 4S2M Sensor All Wheels Two Modular Valves

Parking Brake Spring Brake on All Axles

OPTIONS

Additional Deck Length & Width (20'-21'-22'-23'-24' Optional Lengths) (96" Optional Width) Additional "ROTO-RINGS"®

Tool Box Lid (Lockable) Optional: Expanded Metal Tray Plate Spare Tire & Rim 215/75R 17.5 (H) Optional: Spare Tire Carrier

Traction 2" x2" Angle 6" C/C Wheel Paths Optional: Traction Center Section, Bucket Pocket or Plate

Ramps Wood (standard); Ladder (Optional N/C); Electric-Hydraulic 36" Wide x 8' Long

Extension Ramps T-6 Alum. 22" x 75" 8-degree angle (SET)

Parking Jack Optional: Jack mounted on Headboard

Apitong Decking in lieu of Oak

Paint (other than standard Black, Yellow, Blue) Price on Request

