



### SPECIFICATIONS

**Capacity:** 50,000 lbs. **Trailer Weight:** 11,720 lbs.

|                |  |
|----------------|--|
| Deck Width     | 8 ft. 6 in. Length: 22 ft. Height: 34 in.  |
| Frame          | Mainrails: W14" x 26 lbs. wide flange I-Beam, one piece cold formed Hi-tensile 50,000 P.S.I. steel mainrails from front to drawbar to rear of trailer<br>8° Beaver Tail (Safe Low Loading Angle) |
| Crossmembers   | 6" x 9 lbs. per ft. I-Beam pierced through mainbeam  |
| Decking        | Nominal 2" Hardwood  |
| Headboard      | 8" high, full width of trailer Drawbar Storage Area  |
| Lights         | Sealed L.E.D., 12 volt, DOT approved   |
| Wiring Harness | USA Star PLUS Sealed Modular Wiring Harness w/ 7-Way ATA Plug  |
| Hitch          | One piece solid cast steel (adjustable) lunette eye & flange mount   |
| Safety Chains  | Two 1/2" Blue-Krome plated high test, safety hook w/ latch   |
| Parking Jack   | 70,000 lbs. static / 40,000 lbs. lift, (Heavy Duty 2-Speed screw type)   |
| Tie Down       | Six per side - Patented "ROTO RINGS"® Swivel 360°  |
| Colors         | Black, Yellow, Blue (standard) Imron Paint   |

### RUNNING GEAR

|               |   |
|---------------|---|
| Tires         | Twelve 215/75R17.5 (H) Steel Belted Radial  |
| Hubs/Wheels   | Six Disc Type Hubs, Twelve 6.75 x 17.5, 8-Bolt, Hub-Piloted Disc Wheels             |
| Suspension    | Hutch H-9700, Three leaf, capacity 75,000 lbs. Tri-axle                             |
| Axles         | Three 5" diameter 22,500 lbs. each, H.M. series bearings (maximum axle track width) |
| ALL WHEEL ABS | Anti-Lock Brake System 4S3M Sensors on (2) Axles Three Modulator Valves             |
| Parking Brake | Spring Brakes on All Axles  |

### OPTIONS

Additional Deck Length & Width (23'-24'-25' Optional Lengths) (96" Optional Width) Additional "ROTO-RINGS"®  
Tool Box Lid (Lockable) Optional: Expanded Metal Tray Plate  
Spare Tire & Rim 215/75R17.5 (H) Optional: Spare Tire Carrier  
Traction 2" x 2" Angle 6" C/C Wheel Paths Optional: Traction Center Section, Bucket Pocket or Plate  
Ramps Wood (standard); Ladder (Optional N/C); Electric-Hydraulic 36" Wide x 8' Long  
Extension Ramps T-6 Alum. 22" x 75" 8-degree angle (SET)  
Parking Jack Optional: Jack mounted on Headboard  
Apitong Decking in lieu of Oak  
Paint (other than standard Black, Yellow, Blue) Price on Request

