



SPECIFICATIONS

Capacity: 140,000 lbs. **Trailer Weight:** 28,640 lbs.

Deck Width	8 ft. 6 in. Height: 43in. (Loaded) Overall Length: 57 ft. 0in. (with 110" swing neck)
Frame	Mainrails: fabricated 24" Deep I-Beam. Siderails: fabricated 16" Deep I-Beam
Crossmembers	10" x 12 lbs. per ft. I-Beam, pierced through mainbeam (18" spacing)
Decking	2" Nominal Apitong wood ahead of wheels, 3/8" smooth steel over wheels
Tail Roller	Bolt on Tail Roller with Weevil Pockets and two support rollers
Fairlead Roller	Fairlead Roller in Rear of Gooseneck with Weevil Pockets
Winch Loop	Winch Loop on Front of Gooseneck with Full Width Integrated Skid Pipe
Weevil Pockets	Mounted every 6 ft on Outside of Side Rail and on one Bolster
Wiring Harness	Sealed LED Lights & USA Star PLUS Sealed Modular Wiring Harness
Gooseneck	4" Relief Style and 102" Swing Clearance STD (Other Lengths Available)
Tie Down	Eight Roto Rings Per Side; Fixed D-Rings on Rear of Neck and Tailboard
Colors	Yellow, Red, Black with matching Undercoating

RUNNING GEAR

Tires	Twenty 255/70R22.5 (H) Steel Belted Radial (Yokohama)
Hubs/Wheels	Disc Type Hubs, 8.25 x 22.5 Disc Type Wheels, Stemco Oil Seals, Hub Piloted
Suspension	Air Ride (Combined Capacity 125,000 lbs) with Dump Valve; Lift 1st & 2nd Axle
Axles	Five 5" Diameter 25,000 lbs. each, H.M. series bearings
Brakes	16 1/2" x 7" Air, "S" Cam, Automatic Slack Adjusters
All Wheel ABS	Anti-lock brake system 4S3M, Sensors on (2) Axles, 3 Modulator Valves
Parking Brake	Spring Brakes on All Wheels

OPTIONS

- Air Lift Deck Rollers – one set 2' Forward of Suspension, one set 6' aft of Gooseneck
- Four Inch Dia. stanchion pockets (81" between) – one set 4' aft of Gooseneck, one set on forward Bolster, includes stanchion pipes and stanchion pipe rack on Gooseneck
- Lockable Toolbox in Gooseneck and Expanded Metal Floor in Gooseneck
- Additional Gooseneck Lengths and Heights
- Inverted 5th Wheel
- Heavy Duty Drop Leg Supports
- Dual Air & Electrical Connections - Front of GN and Front of Bed
- Manual Raise and Lower Valve
- Oak Decking in lieu of Apitong
- Aluminum Wheels
- Spare Tire Carrier with or without Mounted Spare
- Tire & Disc Wheel 275/70R22.5 (H) Upgrade (Yokohama)

